

Rigid Pneumatic Wheel Roller RP930

Benefits:

- 6 Cylinder 152 HP turbo diesel engine
- Three Speeds: 0-6, 0-8, 0-12 mph
- Hydrostatic drive
- 30 Ton rigid frame
- · Full wheel oscillation insures uniform densities
- Electronic displacement control (EDC) propel
- · Side to side seat slide and 180° seat rotation
- · Easily accessible engine bay under spring assist hood



Benefits:

Ballast Capacity	
Weights	Empty 28,500 lbs With water 46,800 lbs With sand (dry) 57,500 lbs With sand (wet) 63,300 lbs
Loads per Tire	Empty 3,166 lbs With water 5,200 lbs With sand (dry) 6,388 lbs With sand (wet) 7,033 lbs
Engine	Cummins, 6 cylinder turbo diesel producing 152 hp @ 2500 RPM. 12 volt electrical system; 63 amp alternator. Muffler. Two stage air cleaner with filter condition indicator and vacuator valve.
Wheels	11.00 X 20, 18 ply

Hydrostatio	C
Drive	

The hydrostatic drive consists of a variable displacement piston pump and two planetary drive wheel motors. In this closed loop circuit the fluid is filtered through a 10 micron filter and returned to the reservoir passing through an oil to air heat exchanger.

Fuel System

50 U.S. gal. (124.9 liters)

Sprinkler System

Optional

The 3 position "Memory Water" spray control gives the operator a helping hand.

Position 1 - Turns the system off.

Position 2 - Allows the spray system to operate continuously.


Position 3 - Automatically turns the spray system on whenever the machine is in motion, then turns it off when the machine is brought to a stop!

Speeds and Controls

Infinitely variable speed forward and reverse 0-12 MPH. Speed, direction and dynamic braking are controlled by a single lever.

Standard Equipment

Diesel engine. 18 ply tires. Cushioned adjustable seat. Horn. Seat Belts. Vandalism package. Water ballast covers. Neutral safety starter interlock. Parking brake starter interlock. Yellow Paint. Backup alarm. Engine shutdown systems. ROPs.



Dimensions:

without	ontions
williout	UDUUIIS

A. Wheel base
B. Overall length
C. Overall height
D. Height w/ROPS
E. Rolling width
F. Body width
G. Outside turning radius 24' 5"
H. Inside turning radius
I. Ground clearance
J. Tire overlap

Optional Equipment:

Beacon light

Nylon scraper

Skirt package

Lighting package including:

Rear working lights (2)

Front working lights (2)

Turn signals

Fog spray system (sprinkler system)

Cocomats

Cold weather start package

Sold & Serviced by:



Ingram Compaction, LLC 2823 Carlisle Ave. Racine, WI 53404

Toll Free: 800-288-8629 e-mail: info@ingramrollers.com

www.ingramrollers.com